



## PRODUCT DATA SHEET

Laser Diode (HHL w/window package)

Model FB-M1450-1500HO

Specification	Symbol	Typical	Unit
Laser Emitter			
Peak Wavelength	$\lambda_{op}$	$1450 \pm 10$	nm
CW Optical Output Power	$P_{op}$	1.5	W
Operation Current	$I_{op}$	$<4.5$	A
Operation Voltage	$U_{ld}$	$1.1 \pm 0.1$	V
Threshold Current	$I_{th}$	$< 0.9$	A
Beam Divergence (FWHM)	$\theta_{\parallel}$	$16 \pm 3$	degree
Beam Divergence (FWHM)	$\theta_{\perp}$	$1 \pm 0.3$	degree
Spectrum Half-Width (FWHM)	$\Delta\lambda$	$< 7$	nm
Emitting Area	$W_{xd}$	100x1	$\mu\text{m} \times \mu\text{m}$
Operation Mode	-	CW, QCW, Pulse ( $\tau > 5\text{ns}$ )	-
Operation Temperature	Top	25	degree
Photo Diode Monitor			
PD Monitor Current		1-1000	$\mu\text{A}$
PD Reverse Voltage		9	V
TEC			
Maximum Current		5	A
Maximum Operation Voltage		3,8	V
Thermistor			
Resistance		10	kilohm
Wavelength Temperature Coefficient	$\Delta\lambda/\Delta T$	$4 \pm 0.5$	$\text{\AA}/\text{degree}$
Operation Current Temperature Coefficient	$\Delta I/\Delta T$	$20 \pm 5$	$\text{mA}/\text{degree}$
Operation Temperature Range		-20... +40	degree
Storage Temperature Range		-40... +80	degree



## Drawings:

