



## PRODUCT DATA SHEET

Laser Diode

Model FB-S1060-200SOT148

Specification	Symbol	Typical	Unit
Laser Emitter			
Peak Wavelength	$\lambda_{op}$	1060±10	nm
CW Optical Output Power	$P_{op}$	200	mW
Operation Current	$I_{op}$	<350	mA
Operation Voltage	$U_{Id}$	1.6±0.1	V
Threshold Current	$I_{th}$	<130	mA
Beam Divergence (FWHM)	$\theta_{  }$	9±3	degree
Beam Divergence (FWHM)	$\theta_{\perp}$	25±5	degree
Spectrum Half-Width (FWHM)	$\Delta\lambda$	<5	nm
Emitting Area	$W \times d$	5x1	$\mu\text{m} \times \mu\text{m}$
Wavelength Temperature Coefficient	$\Delta\lambda/\Delta T$	3.5±0.2	Å/degree
Operation Power Temperature Coefficient	$\Delta P/\Delta T$	0.2±0.05	mW/degree
Mode Structure	SM	$TE_{00}$	-
Operation Temperature	$T_{op}$	25	degree
Operation Temperature Range		-40... +50	degree
Storage Temperature Range		-40... +80	degree
Operation Mode	CW Pulse	Continuous Wave Pulse, $\tau > 5$ ns	-
Photo Diode Monitor			
Monitor Current		1-1000	$\mu\text{A}$
PD Reverse Voltage		<5	V

*Note: To guarantee reliable operation of laser diode TO-Can (9mm) package must be mounted onto copper carrier with TEC (Peltier element) keeping constant temperature.*



Drawings:

